

888

Portable Production Mixer-Recorder



Specifications

Analog Inputs

- **Frequency Response**
 - 10 Hz to 80 kHz \pm 0.5 dB (192 kHz sample rate, re 1 kHz)
- **THD + Noise**
 - 0.005% max (mic in, 1 kHz, 22 Hz–22 kHz BW, trim at 20, fader at 0, -10 dBu in)
- **Equivalent Input Noise**
 - -131 dBV (-129 dBu) max (mic in, A-weighting, 76 dB gain, 150 ohm source impedance)

Processing Engine

- Highly extensible, full FPGA-based audio processing, 3 FPGAs
- Six-way ARM multiprocessor system
- 64-bit audio processing precision

Audio Over Ethernet

- Dante, AES67 compatible
- 16 Channels in, 16 channels out (up to 96 kHz)
- 1 Gb/s Ethernet, 1 port, transformer-balanced

Inputs

- **Mic/Line inputs**
 - 8 total, all fully featured; 4 on full-size XLR, 4 on TA3
- **Inputs**
 - Mic-level inputs: (XLR, TA3): Class-A, discrete differential long-tail pair, 4k ohm input impedance
 - Line-level inputs: (XLR, TA3): active-balanced, 4k ohm input impedance
 - 48 V phantom: full 10 mA to all 8 inputs simultaneously
 - 12 Total analog inputs: 8 mic-line inputs, 4 on returns
 - AES3 or AES42 available on XLR input 1
 - AES42: +10 V, 250 mA available, mode-1, auto-ASRC
 - USB Audio: 2 Inputs
 - Rtn A (TA3): unbalanced 2-channel, 4k ohm input impedance
 - Rtn B (3.5 mm): unbalanced 2-channel, 4k ohm input impedance
 - Com Rtn (TA3) balanced, 1-channel, 8k ohm input impedance
 - External Slate Mic (TA5): balanced, 8k ohm input impedance
- **Maximum Input Level**
 - Mic: +8 dBu (2.0 Vrms)
 - Line: +28 dBu (19.5 Vrms)
 - Rtn A, B: +18 dBu (6.2 Vrms)
 - Com Rtn: +24 dBu (12.3 Vrms)
 - External Slate Mic: +12 dBu (3.2 Vrms)

Buses

- 10 Buses (L, R, 1-8)
- Left and Right Mix Bus receives post-fade isolated channels. Optional NoiseAssist plugin instances can be applied to any bus. Buses 1-8 can receive

High-Pass Filters

- Adjustable 10 Hz to 320 Hz, 18 dB/oct. 1st stage analog (before preamp), 2nd stage digital.

Limiters

- Limiters available at all channels, buses, headphones, for all sample rates
- Analog first stage, all subsequent stages digital
- Attack time: adjustable 1 to 200 ms
- Release time: adjustable, 50 ms to 1000 ms
- Threshold: adjustable, -2 dBFS to -12 dBFS
- Selectable ratio: inf:1, 20:1, 18:1, 16:1, 14:1, 12:1, 10:1
- Knee: soft, hard

Compressors

- Compressors available at all channels (pre or post-fade) and buses for all sample rates
- Attack time: adjustable, 1 to 200 ms
- Release time: adjustable, 50 ms to 1000 ms
- Threshold: adjustable, 0 dBFS to -40 dBFS
- Selectable ratio: adjustable, 1:1 to 20:1
- Knee: soft, hard

Delay

- Channel Adjustable 0-50 ms
- Output Adjustable 0-500 ms

Maximum Gain

- Trim stage (mic input): 76 dB
- Trim stage (line input): 50 dB
- Fader stage: 16 dB
- Bus stage: 16 dB
- Headphone stage: 20 dB
- Mic-to-Line: 108 dB
- Mic-to-Headphone: 112 dB

Outputs

- **Outputs**
 - XLR (L, R) active-balanced, 250/3.2k/120 ohms (mic/-10/line)
 - TA3 (X1-X4) active-balanced, 250/3.2k/120 ohms (mic/-10/line)
 - 3.5mm (X5, X6, X7, X8): unbalanced, stereo, 1.8k ohms
- **Headphone Outputs**
 - ¼", 3.5 mm
 - TA5 (along with mic input pins) for single connection to headset + mic
 - High output, 4 ohm output impedance, 400 mW + 400 mW at each connector, all individually driven
 - Compatible with headphones of any impedance
- **Maximum Output Level (all into 10k load)**
 - Line: +20 dBu (7.8 Vrms)
 - "-10": +6 dBu (1.5 Vrms)
 - Mic: -20 dBu (0.078 Vrms)
 - X5/X6 Out: +6 dBu (1.5 Vrms)
 - Headphone outputs (¼", TA-5, X7/X8): +14 dBu (4.0 Vrms)
- **Digital Outputs**
 - AES3 transformer-balanced, in pairs; 1-2 (XLR-L), 3-4 (XLR-R),
 - 110 ohm, 2 V p-p, AES and S/PDIF compatible

Recording

- **A/D Converters**
 - 32-bit, 120 dB, A-weighted dynamic range typical
 - Sampling rates 44.1 kHz, 47.952 kHz, 48 kHz, 48.048 kHz, 96 kHz, 192 kHz
- **Bit Depth**
 - 16, 24
- **Recording**
 - Internal 256 GB SSD; two removable SD Cards. Each 10% over-provisioned (reserved free space) for optimum performance
 - Simultaneous recording to internal SSD and the two SD cards
 - exFAT formatting
 - 20 tracks (16 iso channels, 4 buses)
 - Broadcast WAV monophonic and polyphonic file format
 - 64-bit WAV (RF64) monophonic and polyphonic; support for files > 4 GB
 - AAC 2 track at 48 kHz, selectable bit rate 32, 64, 128, 192, 256 kbps

Automatic Mixing

- Dugan Automixer/MixAssist up to 16 channels on Left and Right Mix bus
- MixAssist up to 16 channels on Left and Right Mix bus

Noise Suppression

- Via optional paid Sound Devices NoiseAssist or CEDAR sdnx Plugins
- Two, four, or eight instances of Noise Suppression can run on any combination of isolated channels (excluding 17-32 on Scorpio), or buses.
- Attenuation range: 0-20 dB
- NoiseAssist operates with sampling rates of 44.1 kHz to 48.048 kHz.
- CEDAR sdnx operates with sampling rates of 44.1 kHz to 96 kHz.
- NoiseAssist audio path latency: 0.77 ms @ 48kHz
- CEDAR sdnx audio path latency: 0.27 ms @ 48kHz, 0.14ms @ 96kHz

USB

- USB-C (USB 3.1 type 1) for file transfer of internal SSD, both SD Cards
- USB-C 2-in/2-out USB audio interface
- USB-A host for keyboard, external controller, external USB hubs supported for connecting multiple devices

Timecode and Sync

- Modes Supported: Off, Rec Run, Free Run, 24h Run, External, including External Auto-Record and Continuous modes.
- Frame Rates: 23.98, 24, 25, 29.97 DF, 29.97 ND, 30 DF, 30 ND
- Sample/Timecode Accuracy: 0.1 ppm (0.25 frames per 24 hours)
- Timecode Input: 20k ohm impedance, 0.3 V – 3.0 V p-p (-17 dBu – +3 dBu)
- Timecode Output: 75 ohm impedance, 5 V p-p (+7 dBu)

Remote Control

- Sound Devices CL-16 Linear Fader Controller
- Sound Devices CL-12 Linear Fader Controller
- USB MIDI MCU Control – supported 3rd party fader controllers
- SD-Remote Android Tablet app via USB or Bluetooth LE
- SD-Remote Android Phone app via Bluetooth LE
- SD-Remote iPad and iPhone app via Bluetooth LE
- USB Keyboard
- External Timecode Record Trigger

File Delivery to Cloud

- Compatible with Frame.io Camera to Cloud
- Compatible with Viviana Cloud

LCD

- 320x240, Transflective, excellent sunlight visibility
- Larger touchscreen display available via USB-connected SD-Remote app

Power

- External: 10-18 V input on locking TA4 connectors, (pin 4 positive, pin 1 ground), supports Smart Battery telemetry
- Dual rear-mount Sony-style L-mount batteries with chargers
- **Current Draw, at 12 V no battery charging**
 - All mic preamps off: 980 mA
 - All mic preamps on: 790 mA
 - All mic preamps on, 192 kHz sample rate, recording to 2 SD Cards: 1.13 A
 - All mic preamps on, 192 kHz sample rate, recording to 2 SD Cards, Dante enabled: 1.38 A
- Intelligent power-down of unused mic preamps and other internal circuits

Environmental

- Operating: -20° C to 60° C, 0 to 90% relative humidity (non-condensing)
- Storage: -40° C to 85° C

Dimensions (H x W x D)

- 5.1 cm x 24.5 cm x 18.5 cm
- 2.0 in. x 10.0 in. x 7.3 in

Weight

- 4.0 lbs (unpackaged, without batteries)
- 1.83 kg (unpackaged, without batteries)